



GUIDE - CONNECTION TWO PHONES SIMULTANEOUSLY WITH COM-DEX

Important information

As of June 2016, COM-DEX is available with two different firmware versions: version 1.0.10 and version 1.2.0.

Only firmware version 1.2.0 (and newer) can connect to two phones simultaneously.

To see which firmware version your COM-DEX has, connect it to a Bluetooth phone running the App, which is available for iOS and Android. In the App, go to More | Help | App and device information -> COM-DEX firmware version.

IMPORTANT: We strongly recommend only installing and using the App on **one** phone when using COM-DEX with two phones.

Quick guide for connecting two phones with COM-DEX

To connect two phones with COM-DEX for the first time:

- 1. COM-DEX must have firmware 1.2.0 or newer
- 2. Ensure that COM-DEX is on (neck loop closed) and not connected to any Bluetooth device (LED will flash blue-red)
- 3. Reset COM-DEX by holding down both buttons for 5 seconds and then open the neck loop for 10 seconds.
- 4. Connect phone #1 to COM-DEX via Bluetooth
- 5. Disable Bluetooth on phone #1. The Light Emitting Diode (LED) on COM-DEX will start flashing red and blue
- 6. Connect phone #2 to COM-DEX via Bluetooth
- 7. Enable Bluetooth on phone #1 again and if necessary manually reconnect to COM-DEX in the Bluetooth menu. COM-DEX is now connected to both phones via Bluetooth.
- 8. If desired, start the App on the preferred phone. Remember to only run the App on *one* phone. (The App is not necessary in order to use COM-DEX with two phones).

Subsequent connections:

a. COM-DEX will automatically connect to phone #1 and #2 if they are available when the COM-DEX neck loop is closed. It might be necessary to connect manually in the Bluetooth menu.

${\Bbb C}{\Bbb O}{\Bbb M} ext{-}{\Bbb D}{\Bbb E}{f X}$ **- connecting two phones**

SEPTEMBER, 2016



Detailed guide for connecting two phones with COM-DEX

As a precaution it is recommended to reset COM-DEX and to clear the internal paring list in COM-DEX. To do this:

- 1. Close the COM-DEX neck-loop.
- Disconnect/turn off all Bluetooth devices, which are connected to COM-DEX.
 When done correctly, the LED on the side of the COM-DEX will flash red and blue.
- 3. Hold down the Push- and Room Off button for 5 seconds until the blue-red flashing pattern is briefly interrupted by a constant red light.
- 4. Open the neck-loop and leave it open for at least 10 seconds. This will reboot COM-DEX.

If you are using the App make sure you have identified which phone you want to run it on.

- 1. Close the neck-loop. The LED will flash red and blue to indicate that no phone is connected to COM-DEX.
- 2. Open the settings menu on phone #1
- 3. Go to Bluetooth settings on phone #1 and make sure Bluetooth is turned on. A search list of Bluetooth devices should appear.
- 4. When your COM-DEX appears on the Bluetooth search list. Tap on it.
 - a. COM-DEX will be listed as "COM-DEX xxx", where "xxx" correspond to the last three digits in the COM-DEX serial number, which can be found on the back of COM-DEX.
- Phone #1 and COM-DEX are now connected and COM-DEX LED turns off to indicate an established connection.
- 6. Go to Bluetooth settings on phone #1 and disable Bluetooth
- 7. The LED on COM-DEX will start to flash red and blue again to indicate that COM-DEX is ready to connect.
- 8. Repeat step 2-5 with phone #2
- 9. Phone #2 and COM-DEX are now connected
- 10. Re-enable Bluetooth one phone #1. This will in most cases connect phone #1 automatically to COM-DEX
 - a. If, however, the connection to phone #1 is not performed automatically you can force the connection by tapping on "COM-DEX xxx" in the Bluetooth search list of phone #1. See step 4 above.
- 11. Open the neck-loop and leave it open for at least 10 seconds. Then close it again and the COM-DEX will connect to both phones.
- 12. If desired, start the App on the preferred phone. Remember to only run the App on one phone.

